



24" T12 LED LAMP

Linear Fluorescent Retrofit

For: T12 Lamp Replacement

FEATURES AND BENEFITS

- Drop-in replacement for F20T12 and F17T12 lamps
- No fixture modifications needed for retrofit
- Lower power consumption significantly increases life of legacy ballast (can operate with existing ballast)
- Can operate with or without a starter
- Can operate with or without a ballast
- Contains no mercury

PRODUCTSPECIFICATIONS

DESCRIPTION LED Replacement Lamp, 24", T12 **NSN** 6240-01-610-2124 EFO SKU EFO-X024



PRODUCT SPECIFICATIONS

| Lumen Output | 1,150 lm | |
|--------------------------|--|--|
| Wattage | 10W | |
| Efficacy | 115 lm/W | |
| Input Voltage | 115VAC (ballast compatible) | |
| Housing | Unibody aluminum | |
| Lens | Polycarbonate | |
| Weight | 16 oz | |
| Connection | G13 medium bi-pin base | |
| Dimmable | Non-Dimmable | |
| Color Temperature | 4100K | |
| Driver | Integrated electronic driver | |
| Operating Temperature | -25°C to 50°C | |
| Power Factor | 9.9 | |
| Lamp Life | 50,000 hours to 70% lumen maintenance | |
| Manufactured | BAA Compliant | |

COMPATIBLE FIXTURES

| MIL | SLANT | DESCRIPTION | LAMPS PER FIXTURE |
|-------------|-------|--|--------------------------|
| MIL-F-16377 | /8 | Watertight, overhead lighting fixture | 1 |
| | /11 | Watertight, overhead lighting fixture | 2 |
| | /12 | Watertight, overhead lighting fixture | 3 |
| | /57 | Flush mounting with suspended ceilings | 3, 4 and 6 lamp versions |
| | | | |

32000 Aurora Road, Suite B, Solon, OH 44139 • energyfocus.com • 800.327.7877

©2017 Energy Focus, Inc. All Rights Reserved. Energy Focus, Inc. reserves the right to change specifications for product improvement without prior notice.