

LED Hazloc Globe

LED Replacement / LED Fixture

FEATURES AND BENEFITS

- Rugged construction to handle demanding environments
- Longer lasting and better quality of light
- Eliminate time-consuming maintenance
- Rated for Hazardous Location Class 1, Division 2, Groups A, B, C, D
- ABS Type Approved



PRODUCT SPECIFICATIONS

Lumen Output	2,772 lm
Wattage	28.70 W
Efficacy	>95 lm/W
Input Voltage	100-277 VAC (standard voltage option) 347-480 VAC (high voltage option)
Housing	Powder coated aluminum
Lens	Diffused glass
Weight	7 lbs
Mount	Flat or Vessel Mount
Dimmable	Non-dimmable
Color Temperature	4100K
Driver	Field replaceable electronic driver
Operating Temperature	-40°C to 50°C
Power Factor	>.9
Lamp Life	50,000 hours to 70% lumen maintenance
Manufactured	Made in America

ORDERING GUIDE

PRODUCT LINE

LEDGL Hazloc
Globe

PRODUCT LINE

740 70+CRI
4100K

WATTAGE

30HAZ 30W

MOUNT

F Flat
VES Vessel

HIGH VOLTAGE

BLANK Low Voltage
HV High Voltage