



## Small LED Globe Fixture

### LED Replacement / LED Fixture

For: MIL-16377 Standard SYM # 92.2, 93.2, 93.4, 93.5

### FEATURES AND BENEFITS

- Meets all requirements for MIL-DTL-16377
- No vulnerable filament
- Flat/ceiling mounting bracket
- Uses 90% less energy than legacy small globes
- Field repairable
- Watertight and shockproof

### PRODUCT SPECIFICATIONS

Lumen Output	<b>White:</b> 285 lm <b>Red:</b> 127 lm <b>Amber:</b> 151 lm <b>Blue:</b> 28 lm
Wattage	5W
Efficacy	<b>White:</b> 55.5 lm/W <b>Red:</b> 25 lm/W <b>Amber:</b> 29.6 lm/W <b>Blue:</b> 5.2 lm/W
Input Voltage	120VAC, 60 Hz
Housing	A383 aluminum
Lens	Tempered Glass
Weight	5lbs 7oz
Mount	Flat Mount
Dimmable	Not-Dimmable
Color Temperature	N/A
Driver	Field replaceable electronic driver
Operating Temperature	-40°C to 50°C
Power Factor	>.9
Lamp Life	50,000 hours to 70% lumen maintenance
Manufactured	BAA Compliant



### ORDERING GUIDE

#### ENERGY FOCUS

EFO

#### PRODUCT LINE

X001 Small LED  
Globe

#### GLOBE COLOR

**92.2** White  
**93.2** Red  
**93.4** Blue  
**93.5** Amber

#### VERSION

02

#### NSN#

**WHITE**  
6210-01-605-0596  
**RED**  
6210-01-605-0591  
**BLUE**  
6210-01-605-0594  
**AMBER**  
6210-01-605-0590