



## Explosion Proof LED Globe

### LED Replacement / LED Fixture

For: Navy Standard SYM # 48.2 and 68.2

### FEATURES AND BENEFITS

- Explosion-proof tested in accordance with MIL-DTL-16377/25
- Red and white globe versions available
- 80% reduction in energy use compared to legacy solution
- Utilizes legacy bolt pattern
- No vulnerable filament
- Field Replacement: Globe, driver and LED array
- Suitable for use in all Rolls Royce GTG locations

### PRODUCT SPECIFICATIONS

Lumen Output	1,000 lm (white)
Wattage	19 W
Efficacy	52.6 lm/W (white)
Input Voltage	115 VAC nominal, 60 Hz
Housing	A356-T6 aluminum
Lens	Tempered Glass
Weight	12 lbs 8 oz
Mount	Surface Mount
Dimmable	Not-Dimmable
Color Temperature	4100K
Driver	Field replaceable electronic driver
Operating Temperature	-40°C to 93°C
Power Factor	>.9
Lamp Life	50,000 hours to 70% lumen maintenance @ 200°F (93°C)
Manufactured	BAA Compliant



### ORDERING GUIDE

#### ENERGY FOCUS

EFO

#### PRODUCT LINE

**X008** Explosion Proof  
LED Globe

#### GLOBE COLOR

**48.2** White  
**68.2** Red

#### VERSION

01

#### NSN #

**WHITE - 6210-01-652-8955**  
6210-01-652-8953 LED ARRAY  
6130-01-652-8957 LED DRIVER  
6210-01-652-8954 GLOBE GLASS  
**RED - 6210-01-652-8956**  
6210-01-652-8953 LED ARRAY  
6130-01-652-8957 LED DRIVER  
6210-01-652-8953 GLOBE GLASS