











Intellitube®

LINEAR FLUORESCENT RETROFIT LAMP

For: T8 lamp replacement

FEATURES AND BENEFITS

- Proprietary Universal Design- Direct Fit or Direct Wire Application
- Direct Fit for plug-and-play replacement of a fluorescent lamp. For ballast compatibility visit energyfocus.com
- Direct Wire for highest efficiency and lowest energy cost
- Quick and simple lighting upgrade

Intellitube® is a universal all-in-one lamp that offers both Direct Fit and Direct Wire functions. In Direct Fit mode, it serves as a one-for-one replacement of an existing fluorescent lamp. In the event of a ballast failure, Intellitube® in Direct Wire mode can offer superior efficiency and eliminate the expense of replacing the ballast.



Must use non-shunted lamp holders in Direct Wire Mode

PRODUCT SPECIFICATIONS

Length	2' and 4' versions. Meets ANSI standards				
Body	Oval extruded aluminum/ polycarbonate lens				
Lens	Frosted				
Connection	Medium bi-pin (G13) end cap				
Input Voltage	100-277vac, 50/60hz				
Driver	Integrated LED driver for Direct- Wire mode or external electronic ballast for Direct-Fit mode				
Available colors*	3500K, 4000K, 5000K				
CRI	>80				
Dimming	Direct Fit: compatible with dimming ballast Direct Wired: Non-dimmable				
Lifetime	L70 ≥ 60,000 hours				
Warranty	10-year warranty				
Environmental Requirements	Operating temp: -20° to 50°C Storage temp: -30° to 60°C Working humidity: 30% to 85% Storage humidity: 10% to 90% Non-corrosive environments				
Power Factor	>0.9				
Beam Angle	120°				

Direct Wire Mode: LED tube lamp requires single end power only; wiring to one side of the fixture is sufficient. Ensure lamp end labeled "INPUT" is installed to the live circuit and must use non-shunted lamp holders.





PRODUCT SPECIFICATION

*PART NUMBER	SIZE NOMINAL	POWER	LUMINOUS FLUX	UL PART NUMBER	DLC FAMILY
LEDFLT8-840-208-IT3F	(24") 2'	8W	960lm	3AV10086	JJJMBA
LEDFLT8-835-208-IT3C	(24") 2'	8W	1040lm	3AV10086	JJJMBA
LEDFLT8-835-413-IT3F	(48") 4'	13W	1615lm	3AV10136	JJJMBG
LEDFLT8-840-413-IT3F	(48") 4'	13W	1615lm	3AV10136	JJJMBG
LEDFLT8-840-415-IT3F	(48") 4'	15W	1800lm	3AV10156	JJJMBH

*BUY AMERICAN P/N	SIZE NOMINAL	POWER	LUMINOUS FLUX	UL PART NUMBER	DLC FAMILY
LEDFLT8-840-208-IT3BF	(24") 2'	8W	960lm	3AV10086	JJJMBA
LEDFLT8-840-413-IT3BF	(48") 4'	13W	1560lm	3AV10136	JJJMBG
LEDFLT8-840-415-IT3BF	(48") 4'	15W	1800lm	3AV10156	JJJMBH

^{*}Please contact our Customer Support Department for additional part number configurations

ACCESSORIES

- Single lampholder, no wires (model no. LEDFLSLH-G13NS-SBOG)
- Pair of two (2) lampholders, one with 3' wires (Model no. LEDFLSLH- G13NS-SNETGW)
- Single lampholder, with 3' wires (Model no. LEDFLSLH-G13NS-SBOGW)

BATTERY PACK COMPATIBILITY

- Energy Focus Emergency Battery Pack in Direct Wire installations (model no. LEDES-PWR25-90M)
- See list for emergency ballast compatibility at www.energyfocus.com

