



LED Commercial Downlight

Energy Focus LED Commercial Downlight has an easy-fit installation using adjustable butterfly clips. The downlight is built with an integral junction box that eliminated the need for traditional recessed housing and mounts directly into the ceiling. The fixture simply gets wired to a wall switch and places into the ceiling - no can, bulb, or extra labor required! It is designed and engineered for commercial and public spaces such as shopping malls, hospitals, airports, hotel lobbies, etc.

FEATURES AND BENEFITS

- Twist-lock modular design
- Integrated J-box for direct-wire, eliminated recessed can
- CCT and wattage adjustable

PRODUCT SPECIFICATIONS

Width	4", 6", 8" and 10" versions
Body	Aluminum
Lens	Specular aluminum reflector with frosted/diffuse lens
Mounting	Butterfly clips
Input Voltage	100-277 VAC 120 VAC (only Triac dimming)
Driver	External
Available colors	CCT-Switchable between 3500K, 4000K, and 5000K
CRI	>80
Dimming	1-10V Dimming
Lifetime	5-year warranty
Environmental Requirements	Operating temp: -20° to 50°C Storage temp: -30° to 60°C Working humidity: 30% to 85% Storage humidity: 10% to 90% Non-corrosive environments
Power Factor	>0.9
Beam Angle	4" = TBD° 6" = TBD° 8" = TBD° 10" = TBD°



PRODUCT SPECIFICATION

PARTNUMBER	SIZE	NOMINAL POWER	LUMINOUSFLUX
TBD	4"/6"/8"/10"	20W/15W/10W	TBD
TBD	4"/6"/8"/10"	40W/34W/27W	TBD

