

	PROJECT:	NOTES:
/	DATE:	
E	PART #:	
	REP:	

# **RedCap<sup>®</sup> Emergency Battery Backup LED Tube**

T8 LINEAR FLUORESCENT RETROFIT LAMP WITH EMERGENCY BACKUP CAPABILITIES



The Energy Focus RedCap® Emergency Battery Backup is an all-in-one general purpose lighting and battery powered emergency backup TLED solution. The tube acts as a normal lamp, providing 110 lm/W efficacy and supporting on/off switch operation.

## FEATURES

- Energy Focus patented design standard input end powers the lamp in normal mode, and the emergency input end charges the batteries and senses the presence of AC power
- Integrated batteries and emergency driver provide 960lm of light for a minimum of 90 minutes
- · Batteries charge even when lamps are off
- Emergency and standard fluorescent ballasts can be removed
- Integrated test button

#### WARRANTY

5-year standard warranty (further details available at <u>www.energyfocus.com</u>)

# IDEAL APPLICATIONS

- Offices
- Retail Stores
- Schools

- Hospitals
- Healthcare Facilities
- Industrial/Manufacturing Sites
- Anywhere a fluorescent or LED emergency fixture is used



32000 Aurora Rd Solon, OH 44139 • 800-327-7877 • <u>www.energyfocus.com</u> • <u>orders@energyfocus.com</u>

©2023 Energy Focus, Inc. All Rights Reserved. Energy Focus, Inc. reserves the right to change specifications for product improvement without prior notice.



# RedCap<sup>®</sup> Emergency Battery Backup LED Tube


T8 LINEAR FLUORESCENT RETROFIT LAMP WITH EMERGENCY BACKUP CAPABILITIES

## SPECIFICATIONS

ITEM	SPECIFICATION	SPECIFICATION DETAILS	
	CRI	>80	
GENERAL	Beam Angle	120°	
PERFORMANCE	Rated Life	≥ 50,000 hours	
	Battery Charge Power	16W (charging)	
	Power Factor	>0.9	
ELECTRICAL	Input Voltage	120-277vac, 50/60hz	
	Dimming	Dimmable	
	Base Type	G13	
	Body	Oval extruded aluminum	
	Lens	Polycarbonate	
PHYSICAL	Driver	Single end power; integrated LED driver	
	Operating Temperature	0°C to 40°C	
	Storage Temperature	-20°C to 30°C	
	Relative Humidity	45% to 85%	
	Warranty	5-year standard warranty	
QUALIFICATION	IES File	IES file download	

#### DIMENSIONS

#### 1.49" X 1.14" X 47.8"(37.8MM X 28.9MM X 1212MM)



32000 Aurora Rd Solon, OH 44139 • 800-327-7877 • www.energyfocus.com • orders@energyfocus.com

©2023 Energy Focus, Inc. All Rights Reserved. Energy Focus, Inc. reserves the right to change specifications for product improvement without prior notice.



# RedCap<sup>®</sup> Emergency Battery Backup LED Tube


T8 LINEAR FLUORESCENT RETROFIT LAMP WITH EMERGENCY BACKUP CAPABILITIES

#### ORDERING


PART #	LENGTH	WATTAGE	NORMAL LUMENS	EMERGENCY LUMENS	ССТ	LENS
LEDFLT8-835-414-BBUF	(48") 4'	14W	1595lm	960lm	3500K	Frosted
LEDFLT8-840-414-BBUF	(48") 4'	14W	1595lm	960lm	4000K	Frosted
LEDFLT8-850-414-BBUF	(48") 4'	14W	1595lm	960lm	5000K	Frosted

To view our DLC Qualified products, please consult the DLC Qualified products list at www.designlights.org/qpl

# SINGLE LAMP WIRING DIAGRAM



#### MULTIPLE LAMP WIRING DIAGRAM



To view full installation instructions, visit the product page on our website <u>www.energyfocus.com</u>