







LED Replacement/LED Fixture

For: MIL-16377 Standard SYM # 92.2, 93.2, 93.4, 93.5

FEATURES AND BENEFITS

- Meets all requirements for MIL-DTL-16377
- No vulnerable filament
- Flat/ceiling mounting bracket
- Uses 90% less energy than legacy small globes
- Field Replaceable
- Watertight and shockproof

PRODUCT SPECIFICATIONS

Lumen Output	White: 285 lm Red: 127 lm Amber: 151 lm Blue: 28 lm
Wattage	5W
Efficacy	White: 55.5 lm/W Red: 25 lm/W Amber: 29.6 lm/W Blue: 5.2 lm/W
Input Voltage	120VAC, 60 Hz
Housing	A383 aluminum
Lens	Tempered Glass
Weight	5lbs 7oz
Mount	Flat Mount
Dimmable	Not-Dimmable
Color Temperature	N/A
Driver	Field replaceable electronic driver
Operating Temperature	-40°C to 50°C
Power Factor	>.9
Lamp Life	50,000 hours to 70% lumen maintenance
Manufactured	BAA Compliant

ORDERING GUIDE

ENERGY FOCUS	PRODUCT LINE	GLOBE COLOR	VERSION	NSN#
EFO	X001 Small LED	92.2 White	02	WHITE
	Globe	93.2 Red		6210-01-605-0596
	Globe	100		RED
		93.4 Blue		6210-01-605-0591
		93.5 Amber		BLUE
		Join Amber		6210-01-605-0594
				AMBER
				6210-01-605-0590