





Waterline Security Light

LED Replacement/LED Fixture

For: SYM 303.X

FEATURES AND BENEFITS

- · Mounts to existing 2" round post or tongue mount
- Rugged construction to handle demanding environments
- · Longer lasting and better quality of light
- Multiple beam angles available to suit your environment: 25°, 57°
- Cable: 10' SOOW with SYM1218.3 plug
- · Rated for marine use
- ABS Type Approved



PRODUCT SPECIFICATIONS

Lumen Output	11,000 lm		
Wattage	<115W		
Efficacy	>100 lm/W		
Input Voltage	100-277VAC		
Housing	Corrosion resistant aluminum		
Lens	Impact Resistant— Clear (UL94-5VA rated)		
Weight	15 lbs		
Mount	2" diameter round post		
Dimmable	Non-Dimmable		
Color Temperature	4100K		
Driver	Field replaceable electronic driver		
Operating Temperature	-30°C to 50°C		
Power Factor	>.9		
Lamp Life	50,000 hours to 70% lumen maintenance		
Manufactured	BAA Compliant		

ORDERING GUIDE

ENERGY FOCUS EFO	PRODUCT LINE FL Flood Light	BEAM SPREAD 303.3 25°	VERSION 02	NSN 6230-01-665-6332
		303.4 57°	LCS Tongue Mount	