



## Flood & Area Lights

### LED Replacement/LED Fixture

The Flood and Area Light is a mission-ready, energy efficient LED light. It comes in a single or double lens design where customers can choose the beam angle to accommodate a full flood range or a more specified area range.

### FEATURES AND BENEFITS

- Marine use rated
- ABS Type Approved
- Standard bolt pattern on yoke
- Longer lasting and better quality of light
- Eliminate time-consuming maintenance
- Rugged construction to handle demanding environments
- Multiple beam angles available to suit your environment: 14°, 25°, 44°, 57°, 66°

### PRODUCT SPECIFICATIONS

Lumen Output	11,000 lm (single) 22,000 lm (double)
Wattage	<121W (single) <250W (double)
Efficacy	>100 lm/W
Input Voltage	100-277VAC (standard voltage option) 277-480VAC (high voltage option)
Housing	Corrosion resistant aluminum
Lens	Impact Resistant— Clear (UL94-5VA rated)
Weight	15 lbs (single) 24 lbs (double)
Mount	Surface/Rotatable/Yoke
Dimmable	Non-Dimmable
Color Temperature	4100K
Driver	Field replaceable electronic driver
Operating Temperature	-30°C to 50°C
Power Factor	>.9
Lamp Life	50,000 hours to 70% lumen maintenance
Manufactured	BAA Compliant

### ORDERING GUIDE

#### ENERGY FOCUS

EFO

#### PRODUCT LINE

FL Flood & Area  
Light

#### LUMEN OUTPUT

11 11,000  
22 22,000

#### BEAM SPREAD

14 14°  
25 25°  
44 44°  
57 57°  
66 66°

#### HIGH VOLTAGE

BLANK Standard Voltage  
HV High Voltage